



dynamic polymers

Offering a complete line of wax based raw materials

PRODUCT: DYNAMULSION 006A

TECHNICAL DATA SHEET:

DYNAMULSION 006A IS AN ANIONIC EMULSION OF BOILED LINSEED OIL. DESIGNED USING THIS NATURAL OIL IT NOT ONLY ENHANCES A WOODS INHERENT GRAIN PATTERN BUT ALSO, PROVIDES WATER RESISTANCE AND BEADABILITY. DYNAMULSION 006A IS MULTIFUNCTIONAL AND PROVIDES SUPERIOR END USE PROPERTIES INCLUDING:

- **WATER BEADABILITY**
- **WATER RESISTANCE**

PROPERTIES	RANGE
APPEARANCE	TAN LIQUID
SOLIDS TYPE	ORGANIC BOILED LINSEED OIL
NVM %	39.5 - 40.5
PH	7.0 - 9.0
RECOMMENDED PH OF SYSTEM	7.0 - 12.0
VISCOSITY (CPS)	<100

END USE/MARKETS:

- **INTERIOR WOOD COATINGS**
- **EXTERIOR WOOD COATINGS**

STANDARD PACKAGING:

DYNAMULSION 006A IS PACKAGED IN 55 GAL DRUMS & TOTES

This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.