

PRODUCT: DYNAMULSION 19A

TECHNICAL DATA SHEET:

DYNAMULSION 19A IS AN ANIONIC EMULSION OF POLYETHYLENE WAX.
DESIGNED TO BE A MULTIFUNCTIONAL ADDITIVE FOR MAR, RUB, AND
WATER RESISTANCE IN A VARIETY OF INDUSTRIES. DYNAMULSION 19A
PROVIDES SUPERIOR END USE PROPERTIES INCLUDING:

- BLOCK RESISTANCE
- > MOLD RELEASE
- > ABRASION RESISTANCE
- > MAR RESISTANCE

PROPERTIES	RANGE
APPEARANCE	AMBER LIQUID
SOLIDS TYPE	ANIONIC
NVM %	34.5 - 35.5
PH	8.7 - 9.7
VISCOSITY (CPS)	<50

END USE/MARKETS:

- > CONCRETE COATINGS
- > INKS & OPV
- EXTERIOR WOOD COATINGS
- > FURNITURE POLISH
- LEATHER/FABRIC COATINGS

STANDARD PACKAGING:

DYNAMULSION 19A IS PACKAGED IN 55 GAL DRUMS & TOTES

This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.