



# dynamic polymers

Offering a complete line of wax based raw materials

## PRODUCT: DYNAMULSION 5150A

### **TECHNICAL DATA SHEET:**

**DYNAMULSION 5150A IS A CROSSFUNCTIONAL ANIONIC POLYETHYLENE/PARAFFIN BLENDED EMULSION DESIGNED FOR WATER REPELLENCE IN WOOD AND ARCHITECTURAL COATINGS. DYNAMULSION 5150A PROVIDES SUPERIOR END USE PROPERTIES INCLUDING:**

- **WATER RESISTANCE**
- **WATER BEADABILITY**

PROPERTIES	RANGE
APPEARANCE	WHITE LIQUID
SOLIDS TYPE	POLYETHYLENE PARAFFIN BLEND
NVM %	34.5 - 35.5
PH	8.4 - 9.4
VISCOSITY (CPS)	300 - 1500

### **END USE/MARKETS:**

- **LEATHER/TEXTILE COATINGS**
- **ARCHITECTURAL COATINGS**
- **EXTERIOR WOOD COATINGS**

### **STANDARD PACKAGING:**

**DYNAMULSION 5150A IS PACKAGED IN 55 GAL DRUMS & TOTES**

*This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.*