



dynamic polymers

Offering a complete line of wax based raw materials

PRODUCT: DYNAMULSION 63A

TECHNICAL DATA SHEET:

DYNAMULSION 63A IS AN ANIONIC PARAFFIN POLYETHYLENE BLENDED EMULSION DESIGNED FOR LONG TERM WATER BEAD AND WATER RESISTANCE ADDITIVE FOR THE INKS, PAINTS, AND COATINGS MARKETS. DYNAMULSION 63A WAS FORMULATED TO PROVIDE SUPERIOR END USE PROPERTIES INCLUDING:

- **EXCELLENT BLOCK RESISTANCE**
- **WATERBEADING**
- **EXCELLENT BUFFABILITY (AUTOCARE)**
- **EXCELLENT TIRE DRESSING (AUTOCARE)**

PROPERTIES	RANGE
APPEARANCE	LIGHT TAN SEMI-VISCOUS LIQUID
SOLIDS TYPE	POLYETHYLENE PARAFFIN BLEND
NVM %	38.5 - 39.5
PH	9.0 - 10.0
VISCOSITY (CPS)	<1000

END USE/MARKETS:

- **ARCHITECTURAL COATINGS**
- **INKS & OPV**
- **EXTERIOR WOOD COATINGS**
- **AUTOCARE**

STANDARD PACKAGING:

DYNAMULSION 63A IS PACKAGED IN 55 GAL DRUMS & TOTES

This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.