



dynamic polymers

Offering a complete line of wax based raw materials

PRODUCT: DYNAMULSION 7575A

TECHNICAL DATA SHEET:

DYNAMULSION 7575A IS A MULTIFUNCTIONAL LOW VISCOSITY ANIONIC EMULSION DESIGNED FOR WATER RESISTANCE IN WOOD STAINS AND SEALANTS. DYNAMULSION 7575A PROVIDES SUPERIOR END USE PROPERTIES INCLUDING:

- **LOW VOC**
- **EXCELLENT WATERBEADING**
- **USED ALONE OR AS AN ADDITIVE TO SEALANTS**
- **SWELL RESISTANCE**

PROPERTIES	RANGE
APPEARANCE	WHITE LIQUID
SOLIDS TYPE	PROPRIETARY
NVM %	29.0 - 31.5
PH	8.3 - 10.3
VISCOSITY (CPS)	<100

END USE/MARKETS:

- **SEALANTS**
- **EXTERIOR WOOD COATINGS**

STANDARD PACKAGING:

DYNAMULSION 7575A IS PACKAGED IN 55 GAL DRUMS & TOTES

This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.