



dynamic polymers

Offering a complete line of wax based raw materials

PRODUCT: DYNASPERSION 8909N

TECHNICAL DATA SHEET:

DYNASPERSION 8909N IS A VISCOUS NONIONIC DISPERSION OF POLYETHYLENE DESIGNED FOR THE OPV & INK INDUSTRY TO IMPART DESIRED MATTING PROPERTIES TO THE END PRODUCT. DYNASPERSION 8909N PROVIDES SUPERIOR END USE PROPERTIES INCLUDING:

- **FLATTENING**
- **ABRASION RESISTANCE**
- **SCRATCH RESISTANCE**
- **MAR RESISTANCE**

PROPERTIES	RANGE
APPEARANCE	WHITE LIQUID
SOLIDS TYPE	POLYETHYLENE
NVM %	39.0 - 43.0
PH	7.0 - 8.5
VISCOSITY (CPS)	<8500

END USE/MARKETS:

- **INKS**
- **OVERPRINT VARNISHES**
- **INDUSTRIAL COATINGS**

STANDARD PACKAGING:

DYNASPERSION 8909N IS PACKAGED IN 55 GAL DRUMS & TOTES

This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.