



PRODUCT: DP-33

TECHNICAL DATA SHEET:

DYNAMIC POLYMERS DP-33 IS A OXIDIZED POLYETHYLENE WAX THAT HAS BEEN MICRONIZED FOR USE IN PASTE AND SOLVENT BORNE SYSTEMS AND IS DESIGNED TO PROVIDE SUPERIOR END OF USE PROPERTIES INCLUDING:

- **IMPROVED MAR & RUB RESISTANCE**
- **LOWERS/REDUCES C.O.F.**
- **EASE OF DISPERSION**

PROPERTIES	TYPICAL
MELT POINT	225 +/- 10 DEG F
PENETRATION @ 25 DEG C	2.0
AVERAGE PARTICLE SIZE (MICRONS)	8.0
ACID VALUE MG/KOH	8
COLOR	WHITE

END USE/MARKETS:

- **INDUSTRIAL COATINGS**
- **PLASTICS**
- **PRINTING INKS**
- **SPECIALTY APPLICATIONS**

STANDARD PACKAGING:

DP-33 IS PACKAGED IN 15 KG BAGS / 45 BAGS PER PALLET

This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.