



# dynamic polymers

Offering a complete line of wax based raw materials

## PRODUCT: DYNAMULSION 007A

### **TECHNICAL DATA SHEET:**

**DYNAMULSION 007A IS AN ANIONIC EMULSION OF NATURAL TUNG OIL. DESIGNED AS AN ADDITIVE FOR EXTERIOR WOOD AND CONCRETE COATING SYSTEMS DYNAMULSION 007A IS MULTIFUNCTIONAL AND PROVIDES SUPERIOR END USE PROPERTIES INCLUDING:**

- **WATER RESISTANCE**
- **WEATHERABILITY**
- **WATER BEADABILITY**

PROPERTIES	RANGE
APPEARANCE	OFF-WHITE LIQUID
SOLIDS TYPE	ORGANIC TUNG OIL
NVM %	29.5 - 30.5
PH	8.0 - 9.0
RECOMMENDED PH OF SYSTEM	>7.0
VISCOSITY (CPS)	<500

### **END USE/MARKETS:**

- **EXTERIOR WOOD COATINGS**
- **CONCRETE COATINGS**

### **STANDARD PACKAGING:**

**DYNAMULSION 007A IS PACKAGED IN 55 GAL DRUMS & TOTES**

*This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.*