



dynamic polymers

Offering a complete line of wax based raw materials

PRODUCT: DYNAMULSION 009A

TECHNICAL DATA SHEET:

DYNAMULSION 009A IS AN ANIONIC EMULSION OF A NATURAL LINSEED OIL. DESIGNED USING THIS PENETRATING OIL DYNAMULSION 009A NOT ONLY ENHANCES A WOODS INHERENT GRAIN PATTERN BUT PROVIDES WATER RESISTANCE AND BEADABILITY. DYNAMULSION 009A IS MULTIFUNCTIONAL AND PROVIDES SUPERIOR END USE PROPERTIES INCLUDING:

- **WOOD GRAIN ENHANCEMENT**
- **WET LOOK TO STONE**
- **WATER RESISTANCE**

PROPERTIES	RANGE
APPEARANCE	TAN LIQUID
SOLIDS TYPE	ORGANIC LINSEED OIL
NVM %	39.0 - 41.0
PH	7.0 - 9.0
RECOMMENDED PH OF SYSTEM	7.0 - 12.0
VISCOSITY (CPS)	0 - 100

END USE/MARKETS:

- **EXTERIOR WOOD COATINGS**
- **CONCRETE COATINGS**

STANDARD PACKAGING:

DYNAMULSION 009A IS PACKAGED IN 55 GAL DRUMS & TOTES

This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.