



dynamic polymers

Offering a complete line of wax based raw materials

PRODUCT: DYNAMULSION 1228A

TECHNICAL DATA SHEET:

DYNAMULSION 1228A IS AN ANIONIC EMULSION OF PARAFFIN AND POLYETHYLENE WAX. DESIGNED TO BE A MULTIFUNCTIONAL ADDITIVE IN ARCHITECTURAL PAINTS AND COATINGS. DYNAMULSION 1228A PROVIDES SUPERIOR END USE PROPERTIES INCLUDING:

- **ANTIBLOCK PROPERTIES**
- **BLOCK RESISTANCE**
- **IMPROVED WEAR RESISTANCE**

| PROPERTIES | RANGE |
|-----------------|--------------------|
| APPEARANCE | MILKY WHITE LIQUID |
| CHARGE | ANIONIC |
| NVM % | 39.0 - 41.0 |
| PH | 8.5 - 9.5 |
| VISCOSITY (CPS) | <500 |

END USE/MARKETS:

- **ARCHITECTURAL COATINGS**
- **EXTERIOR COATINGS**
- **PRINTING INKS**

STANDARD PACKAGING:

DYNAMULSION 1228A IS PACKAGED IN 55 GAL DRUMS & TOTES

This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.