



# dynamic polymers

Offering a complete line of wax based raw materials

## PRODUCT: DYNAMULSION 2252A

### **TECHNICAL DATA SHEET:**

**DYNAMULSION 2252A IS A MULTIFUNCTIONAL ANIONIC PARAFFIN POLYETHYLENE BLENDED EMULSION FOR APPLICATIONS WHERE GLOSS RETENTION IS IMPORTANT. DYNAMULSION 2252A WAS FORMULATED TO PROVIDE SUPERIOR END USE PROPERTIES INCLUDING:**

- **WEATHERABILITY**
- **EXCELLENT BLOCK RESISTANCE**
- **EXCELLENT GLOSS RETENTION**

<b>PROPERTIES</b>	<b>RANGE</b>
<b>APPEARANCE</b>	<b>AMBER SEMITRANSSPARENT LIQUID</b>
<b>SOLIDS TYPE</b>	<b>POLYETHYLENE PARAFFIN BLEND</b>
<b>NVM %</b>	<b>29.5 - 30.5</b>
<b>PH</b>	<b>9.4 - 10.4</b>
<b>VISCOSITY (CPS)</b>	<b>50 MAX</b>

### **END USE/MARKETS:**

- **CONCRETE COATINGS**
- **INKS & OPV**
- **EXTERIOR WOOD COATINGS**

### **STANDARD PACKAGING:**

**DYNAMULSION 2252A IS PACKAGED IN 55 GAL DRUMS & TOTES**

*This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.*