



## PRODUCT: DYNAMULSION 22N

### **TECHNICAL DATA SHEET:**

**DYNAMULSION 22N IS A MULTIFUNCTIONAL NONIONIC/ANIONIC EMULSION DESIGNED FOR APPLICATIONS REQUIRING A HIGH DEGREE OF SLIP RESISTANCE. THIS PHENOL FREE ADDITIVE IS BEST USED IN FLOOR POLISH AND OVERPRINT VARNISH FORMULATIONS WHEN A HIGH DEGREE OF SLIP RESISTANCE IS NEEDED. IT ALSO PROVIDES DURABILITY AND SCRATCH RESISTANCE IN WOOD APPLICATIONS.**

- **OUTSTANDING DURABILITY**
- **OUTSTANDING ABRASION RESISTANCE**
- **MOLD RELEASE PROPERTIES**
- **PHENOL FREE**

PROPERTIES	RANGE
APPEARANCE	SEMITRANSSPARENT AMBER LIQUID
SOLIDS TYPE	NONIONIC POLYPROPYLENE
NVM %	39.0 - 40.5
PH	7.5 - 9.5
VISCOSITY (CPS)	120 MAX

### **END USE/MARKETS:**

- **INKS & OPV**
- **MOLD RELEASE**
- **EXTERIOR WOOD COATINGS**

### **STANDARD PACKAGING:**

**DYNAMULSION 22N IS PACKAGED IN 55 GAL DRUMS & TOTES**

*This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.*