



dynamic polymers

Offering a complete line of wax based raw materials

PRODUCT: DYNAMULSION 235N

TECHNICAL DATA SHEET:

DYNAMULSION 235N IS A MULTIFUNCTIONAL NONIONIC HIGH DENSITY POLYETHYLENE EMULSION DESIGNED FOR WATER BASED COATINGS AND FLOOR/AUTOMOTIVE POLISHES. THE HIGH DENSITY POLYETHYLENE USED IN DYNAMULSION 235N DICTATES SUPERIOR END USE PROPERTIES INCLUDING:

- **IMPROVED SLIP RESISTANCE**
- **IMPROVED RUB RESISTANCE**
- **IMPROVED MAR RESISTANCE**
- **EXCELLENT TOUGHNESS**

PROPERTIES	RANGE
APPEARANCE	SEMITRANSSPARENT LIQUID
SOLIDS TYPE	HDPE
NVM %	34.0 - 36.0
PH	9.6 - 11.0
VISCOSITY (CPS)	<50

END USE/MARKETS:

- **INDUSTRIAL COATINGS**
- **INKS & OPV**
- **FLOOR & AUTO POLISH**

STANDARD PACKAGING:

DYNAMULSION 235N IS PACKAGED IN 55 GAL DRUMS & TOTES

This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.