



PRODUCT: DYNAMULSION 693A

TECHNICAL DATA SHEET:

DYNAMULSION 693A IS AN ANIONIC PARAFFIN POLYETHYLENE BLENDED EMULSION FOR WOOD COATING APPLICATIONS WHERE MOISTURE RESISTANCE IS IMPORTANT. DYNAMULSION 693A WAS FORMULATED TO PROVIDE SUPERIOR END USE PROPERTIES INCLUDING:

- **EXCELLENT WATER VAPOR RESISTANCE**
- **EXCELLENT WEATHERABILITY**
- **EXCELLENT WATER RESISTANCE**

PROPERTIES	RANGE
APPEARANCE	LIGHT TAN LIQUID
SOLIDS TYPE	POLYETHYLENE PARAFFIN BLEND
NVM %	38.5 - 39.5
PH	9.0 - 10.0
VISCOSITY (CPS)	200 - 275

END USE/MARKETS:

- **INTERIOR WOOD COATINGS**
- **EXTERIOR WOOD COATINGS**

STANDARD PACKAGING:

DYNAMULSION 693A IS PACKAGED IN 55 GAL DRUMS & TOTES

This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.