



dynamic polymers

Offering a complete line of wax based raw materials

PRODUCT: DYNAMULSION 6N

TECHNICAL DATA SHEET:

DYNAMULSION 6N IS A NONIONIC HIGH DENSITY POLYETHYLENE EMULSION DESIGNED FOR HIGH QUALITY AND PERFORMANCE DEMANDING WATER BASED COATINGS APPLICATIONS. DYNAMULSION 6N WAS FORMULATED TO PROVIDE THE VERY BEST END USE PROPERTIES INCLUDING:

- **SUPERB ABRASION RESISTANCE**
- **SUPERB RUB RESISTANCE**
- **SUPERB SCRATCH RESISTANCE**
- **SUPERB BLOCK RESISTANCE**

PROPERTIES	RANGE
APPEARANCE	SEMITRANSSPARENT LIQUID
SOLIDS TYPE	HDPE
NVM %	24.5 - 25.5
PH	4.5 - 7.5
VISCOSITY (CPS)	<15

END USE/MARKETS:

- **INKS & OPV**
- **INDUSTRIAL COATINGS**
- **INDUSTRIAL WOOD COATINGS**

STANDARD PACKAGING:

DYNAMULSION 6N IS PACKAGED IN 55 GAL DRUMS & TOTES

This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.