



PRODUCT: DYNAMULSION 71A

TECHNICAL DATA SHEET:

DYNAMULSION 71A IS A MULTIFUNCTION ANIONIC POLYETHYLENE EMULSION FORMULATED TO IMPROVE PROCESSING AND PERFORMANCE IN DEMANDING COATINGS AND GRAPHIC ARTS APPLICATIONS.

DYNAMULSION 71A IS DESIGNED FOR SUPERIOR SURFACE MODIFICATION PROPERTIES INCLUDING:

- **EXCELLENT MAR, RUB, & BLOCK RESISTANCE**
- **EXCELLENT WATER RESISTANCE**
- **EXCELLENT STAIN AND DIRT RESISTANCE IN CONCRETE**
- **EXCELLENT LUBRICITY IN MOLD RELEASE**

PROPERTIES	RANGE
APPEARANCE	SEMITRANSSPARENT AMBER LIQUID
SOLIDS TYPE	POLYETHYLENE
NVM %	34.5 - 35.5
PH	8.7 - 9.7
VISCOSITY (CPS)	<50

END USE/MARKETS:

- **CONCRETE COATINGS**
- **INTERIOR WOOD COATINGS**
- **EXTERIOR WOOD COATINGS**

STANDARD PACKAGING:

DYNAMULSION 71A IS PACKAGED IN 55 GAL DRUMS & TOTES

This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.