



dynamic polymers

Offering a complete line of wax based raw materials

PRODUCT: DYNAMULSION FJ-2

TECHNICAL DATA SHEET:

DYNAMULSION FJ-2 IS AN ANIONIC EMULSION OF PARAFFIN AND ETHYLENE ACRYLIC ACID COPOLYMER DESIGNED TO PROVIDE IMPROVED PERFORMANCE PROPERTIES IN MULTIPLE APPLICATIONS. SUPERIOR END USE PROPERTIES INCLUDE:

- **WATER RESISTANCE**
- **OPEN TIME**

PROPERTIES	RANGE
APPEARANCE	MILKY WHITE VICOUS LIQUID
SOLIDS TYPE	PARAFFIN/EAA
NVM %	34.5 - 35.5
PH	8.5 - 9.5
VISCOSITY (CPS)	400 - 1800

END USE/MARKETS:

- **CONCRETE COATINGS**
- **EXTERIOR PAINTS & COATINGS**

STANDARD PACKAGING:

DYNAMULSION FJ-2 IS PACKAGED IN 55 GAL DRUMS & TOTES

This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.