

## **PRODUCT: DYNASPERSION 24SP**

## **TECHNICAL DATA SHEET:**

DYNASPERSION 24SP IS AN ACRYLIC RESIN DISPERSION DESIGNED AS A LEVELING AID FLOOR FINISH APPLICATIONS. DYNASPERSION 24SP PROVIDES SUPERIOR END USE PROPERTIES INCLUDING:

- > MAR RESISTANCE
- > BUFFABILITY
- > GLOSS ENHANCEMENT
- > WETTING

PROPERTIES	RANGE
APPEARANCE	WHITE/TAN LIQUID
SOLIDS TYPE	ACRYLIC RESIN
NVM %	29.0 - 31.0
PH	8.2 - 9.7
VISCOSITY (CPS)	200 - 1000

## **END USE/MARKETS:**

- FLOOR FINISHES
- > AUTOMOTIVE POLISH

## **STANDARD PACKAGING:**

**DYNASPERSION 24SP IS PACKAGED IN 55 GAL DRUMS & TOTES** 

This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.