



dynamic polymers

Offering a complete line of wax based raw materials

PRODUCT: DYNASPERSION 410A

TECHNICAL DATA SHEET:

DYNASPERSION 410A IS AN ANIONIC DISPERSION OF POLYETHYLENE DESIGNED TO PROVIDE IMPROVED PERFORMANCE PROPERTIES IN MULTIPLE APPLICATIONS. SUPERIOR END USE PROPERTIES INCLUDE:

- **MAR RESISTANCE**
- **SCRATCH RESISTANCE**
- **BLOCK RESISTANCE**
- **DURABILITY**

PROPERTIES	RANGE
APPEARANCE	MILKY WHITE LIQUID
SOLIDS TYPE	POLYETHYLENE
NVM %	39.5 - 40.5
PH	5.0 - 7.0
VISCOSITY (CPS)	< 500

END USE/MARKETS:

- **INKS**
- **OPV**
- **EXTERIOR WOOD COATINGS**
- **PAINTS**

STANDARD PACKAGING:

DYNASPERSION 410A IS PACKAGED IN 55 GAL DRUMS & TOTES

This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.