



dynamic polymers

Offering a complete line of wax based raw materials

PRODUCT: DYNASPERSION 747AM

TECHNICAL DATA SHEET:

DYNASPERSION 747AM IS AN AMMONIATED DISPERSION OF ETHYLENE ACRYLIC ACID DESIGNED TO PROVIDE IMPROVED PERFORMANCE PROPERTIES IN MULTIPLE APPLICATIONS. SUPERIOR END USE PROPERTIES INCLUDE:

- **ADHESION (METALLIC/CELLULOSIC)**
- **CHEMICAL RESISTANCE**
- **WATER RESISTANCE**
- **HEAT SEAL**

PROPERTIES	RANGE
APPEARANCE	MILKY WHITE LIQUID
SOLIDS TYPE	ETHYLENE ACRYLIC ACID
NVM %	32.0 - 35.0
PH	7.8 - 8.8
VISCOSITY (CPS)	200 - 850

END USE/MARKETS:

- **INKS**
- **OPV**
- **THERMAL TRANSFER**
- **FUNCTIONAL COATINGS**

STANDARD PACKAGING:

DYNASPERSION 747AM IS PACKAGED IN 55 GAL DRUMS & TOTES

This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.