



dynamic polymers

Offering a complete line of wax based raw materials

PRODUCT: DYNASPERSION 90S

TECHNICAL DATA SHEET:

DYNASPERSION 90S IS AN AMMONIATED POLYOLEFIN ACRYLIC HYBRID DISPERSION DESIGNED FOR ANTI CORROSION PRIMERS AND METAL SUBSTRATE SEALER APPLICATIONS. DESIGNED FOR USE METALIC PROCESSING APPLICATIONS DYNASPERSION 90S PROVIDES SUPERIOR END USE PROPERTIES INCLUDING

- **ADHESION PROMOTION**
- **CORROSION RESISTANCE**
- **CHEMICAL RESISTANCE**
- **WATER RESISTANCE**

PROPERTIES	RANGE
APPEARANCE	SEMI-TRANSPARENT LIQUID
EMULSIFIER	AMMONIATED DISPERSION
NVM %	24.0 - 25.5
PH	8.4 - 9.4
VISCOSITY (CPS)	50 - 400

END USE/MARKETS:

- **CAN & COIL COATINGS**
- **METAL/INDUSTRIAL COATINGS**

STANDARD PACKAGING:

DYNASPERSION 90S IS PACKAGED IN 55 GAL DRUMS & TOTES

This information corresponds to the present state of our knowledge and is intended as a general description of the product and its possible application. Dynamic Polymers makes no warranties, express or implied, as to the information's accuracy, adequacy, sufficiency or freedom from defect and assumes no liability in connection with any use of this information. Any user of this product is responsible for determining the suitability of Dynamic Polymers products for its own particular application.